

Page: 1/9

Revised edition no: 2 - 01 Date: 25 / 9 / 2012

Supersedes: 20 / 1 / 2011

Diborane 040

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name : Diborane SDS Nr : 040 Chemical description · Diborane

CAS No :19287-45-7 EC No: 242-940-6 Index No :--

: Registration deadline not expired. Registration-No.

: B2H6 Chemical formula

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.

Test gas / Calibration gas. Chemical reaction / Synthesis.

Contact supplier for more uses information.

Use for manufacture of electronic/photovoltaic components.

Uses advised against : Consumer use

#### 1.3. Details of the supplier of the safety data sheet

: AIR LIQUIDE Deutschland GmbH Company identification Hans-Günther-Sohl-Straße 5

D-40235 Düsseldorf GERMANY

Telefon: +49 (0)211 6699-0 - Fax: +49 (0)211 6699-222

E-Mail address (competent person) : Info.SDB@AirLiquide.de

1.4. Emergency telephone number

**Emergency telephone number** : +49 (0)2151 398668

- Availability : (24/7)

# **SECTION 2. Hazards identification**

# 2.1. Classification of the substance or mixture

# Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

· Health hazards : Acute toxicity, Inhalation - Category 1 - Danger - (CLP : Acute Tox. 1) - H330 · Physical hazards

Flammable gases - Category 1 - Danger - (CLP: Flam. Gas 1) - H220 Gases under pressure - Liquefied gas - Warning - (CLP: Press. Gas) - H280

Classification EC 67/548 or EC 1999/45

Classification : F+: R12 T+; R26

Not included in Annex VI.

# 2.2. Label elements

### Labelling Regulation EC 1272/2008 (CLP)

· Hazard pictograms







In case of emergency: +49 (0)2151 398668

· Hazard pictograms code : GHS06 - GHS02 - GHS04

 Signal words : Danger



Page: 2 / 9

Revised edition no: 2 - 01

Date: 25 / 9 / 2012

Supersedes : 20 / 1 / 2011

040

# **Diborane**

#### **SECTION 2. Hazards identification (continued)**

• Hazard statements : H220 - Extremely flammable gas.

H280 - Contains gas under pressure; may explode if heated.

H330 - Fatal if inhaled.

· Precautionary statements

- Prevention : P260 - Do not breathe gas, vapours.

P210 - Keep away from heat, sparks, open flames or hot surfaces. - No smoking.

- Response : P304+P340+P315 - IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing. Get immediate medical advice / attention.

P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 - Eliminate all ignition sources if safe to do so.

: P403 - Store in a well-ventilated place.

P405 - Store locked up.

2.3. Other hazards

- Storage

Other hazards : None.

# **SECTION 3. Composition/information on ingredients**

#### 3.1. Substance / 3.2. Mixture

Substance.

Substance name		Content [Vol-%]	CAS No EC No Index No Registration no.	Classification(DSD)	Classification(CLP)
Diborane	:	100 %	19287-45-7 242-940-6 	F+; R12 T+; R26	Flam. Gas 1 (H220) Acute Tox. 1 (H330) Liq. Gas (H280)

Contains no other components or impurities which will influence the classification of the product.

- \* 1: Listed in Annex IV / V REACH, exempted from registration.
- \* 2: Registration deadline not expired.
- \* 3: Registration not required: Substance manufactured or imported < 1t/y

Full text of R-phrases see chapter 16. Full text of H-statements see chapter 16

# **SECTION 4. First aid measures**

# 4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep

victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

In case of emergency: +49 (0)2151 398668

Skin contact
 Eye contact
 Adverse effects not expected from this product.
 Adverse effects not expected from this product.

- Ingestion : Ingestion is not considered a potential route of exposure.

# 4.2. Most important symptoms and effects, both acute and delayed

: Delayed adverse effects possible.

Refer to section 11.

#### 4.3. Indication of any immediate medical attention and special treatment needed

: Obtain medical assistance.



Page: 3 / 9

Revised edition no: 2 - 01

Date: 25 / 9 / 2012

Supersedes : 20 / 1 / 2011

040

# **Diborane**

# **SECTION 5. Fire-fighting measures**

#### 5.1. Extinguishing media

- Suitable extinguishing media : Dry powder.

Water spray or fog.

- Unsuitable extinguishing media : Carbon dioxide.

Do not use water jet to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

Specific hazards : Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products : None that are more toxic than the product itself.

5.3. Advice for firefighters

Specific methods : Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive

re-ignition may occur. Extinguish any other fire.

If possible, stop flow of product.

Specialist clean-up methods may be required.

Use fire control measures appropriate to the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering

sewers and drainage systems.

Use water spray or fog to knock down fire fumes if possible.

Special protective equipment for fire

fighters

: Gas tight chemically protective clothing in combination with self contained breathing

apparatus.

Standard EN 137 - self-contained open-circuit compressed air breathing apparatus with full

face mask.

EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid

particles. Gas-tight chemical protective suits for emergency teams.

## **SECTION 6. Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

: Wear self-contained breathing apparatus when entering area unless atmosphere is proved to

be safe.

Ensure adequate air ventilation. Eliminate ignition sources.

Evacuate area.

Prevent from entering sewers, basements and workpits, or any place where its accumulation

can be dangerous. Try to stop release.

Consider the risk of potentially explosive atmospheres.

Monitor concentration of released product.

# 6.2. Environmental precautions

: Try to stop release.

Reduce vapour with fog or fine water spray.

#### 6.3. Methods and material for containment and cleaning up

: Ventilate area.

# 6.4. Reference to other sections

Reference to other sections : See also sections 8 and 13.

Hans-Günther-Sohl-Straße 5 D-40235 Düsseldorf GERMANY Telefon: +49 (0)211 6699-0 - Fax: +49 (0)211 6699-222



Page: 4 / 9
Revised edition no: 2 - 01

Date: 25 / 9 / 2012

Supersedes : 20 / 1 / 2011

**Diborane** 

040

# SECTION 7. Handling and storage

#### 7.1. Precautions for safe handling

Safe use of the product

: Take precautionary measures against static discharge.

Keep away from ignition sources (including static discharges).

Use only properly specified equipment which is suitable for this product, its supply pressure

and temperature. Contact your gas supplier if in doubt. Purge air from system before introducing gas.

Avoid exposure, obtain special instructions before use.

Do not smoke while handling product.

Avoid suck back of water, acid and alkalis.

Only experienced and properly instructed persons should handle gases under pressure. Ensure the complete gas system was (or is regularily) checked for leaks before use. Installation of a cross purge assembly between the cylinder and the regulator is recommended.

Assess the risk of potentially explosive atmosphere and the need for explosion-proof equipment.

Consider the use only non-sparking tools.

The product must be handled in accordance with good industrial hygiene and safety

rocedures.

Consider pressure relief device(s) in gas installations.

Safe handling of the gas receptacle

Refer to supplier's container handling instructions.

Do not allow backfeed into the container.

Replace valve outlet caps or plugs and container caps where supplied as soon as container is

disconnected from equipment.

Protect cylinders from physical damage; do not drag, roll, slide or drop.

Do not remove or deface labels provided by the supplier for the identification of the cylinder

contents

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.)

designed to transport cylinders.

Leave valve protection caps in place until the container has been secured against either a wall

or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating cylinder valve discontinue use and contact

supplier.

Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices.

Keep container valve outlets clean and free from contaminants particularly oil and water.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container.

Damaged valves should be reported immediately to the supplier.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage

Keep container below 50°C in a well ventilated place.

Segregate from oxidant gases and other oxidants in store. Store containers in location free from fire risk and away from sources of heat and ignition. Stored containers should be

periodically checked for general condition and leakage.

Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion. Containers should be stored in the vertical position and properly secured to prevent toppling. Container valve guards or caps should be in place. All electrical equipment in the storage areas should be compatible with the risk of potentially explosive atmosphere. Keep away from combustible

In case of emergency: +49 (0)2151 398668

materials.

# 7.3. Specific end use(s)

: None.



Page: 5 / 9

Revised edition no: 2 - 01

Date: 25 / 9 / 2012

Supersedes : 20 / 1 / 2011

040

# SECTION 8. Exposure controls/personal protection

#### 8.1. Control parameters

**Occupational Exposure Limits** 

Diborane : AGW (8h) - Germany [mg/m³] TRGS 900 : 0.1

Diborane

: AGW (8h) - Germany [ppm] TRGS 900 : 0.1 : Exceeding factor AGW - Germany TRGS 900 : 1

DNEL: Derived no effect level (

Workers)

: None available.

PNEC: Predicted no effect

concentration

: None available.

#### 8.2. Exposure controls

8.2.1. Appropriate engineering

controls

: Provide adequate general and local exhaust ventilation.

Alarm detectors should be used when toxic gases may be released. Systems under pressure should be regularily checked for leakages.

Product to be handled in a closed system and under strictly controlled conditions.

Ensure exposure is below occupational exposure limits (where available).

Consider work permit system e.g. for maintenance activities.

Preferably use only permanent leak-tight installations (e.g. welded pipes).

8.2.2. Individual protection measures, : e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the

risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered.

PPE compliant to the recommended EN / ISO standards should be selected.

• Eye / face protection : Wear safety glasses with side shields or goggles when transfilling or breaking transfer

connections

Wear safety glasses with side shields Standard EN 166 - Personal eye-protection.

- Hand protection : Wear working gloves when handling gas containers.

Standard EN 388 - Protective gloves against mechanical risk

Standard EN 388 - Protective gloves against mechanical risk.

- Other : Consider the use of flame resistant anti-static safety clothing.

Standard EN ISO 14116 - Limited flame spread materials.
Standard EN ISO 1149-5 - Protective clothing: Electrostatic properties.

Wear safety shoes while handling containers.

Standard EN ISO 20345 Personal protective equipment - Safety footwear.

• Respiratory protection : Keep self contained breathing apparatus readily available for emergency use.

Use gas filters and full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers.

Gas filters do not protect against oxygen deficiency.

Gas filters may be used if all surrounding conditions e.g. type and concentration of the

contaminant(s) and duration of use are known.

Standard EN 14387 - gas filter(s), combined filter(s) and full face mask - EN 136.

Consult respiratory device supplier's product information for the selection of the appropriate

device.

Standard EN 137 - self-contained open-circuit compressed air breathing apparatus with full face mask.

Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.

Recommended: Filter B (grey)

Thermal hazards

: None necessary.

8.2.3. Environmental exposure

controls

: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for

In case of emergency: +49 (0)2151 398668

specific methods for waste gas treatment.



Page: 6/9 Revised edition no: 2 - 01

Date: 25 / 9 / 2012

Supersedes: 20 / 1 / 2011

040

# SECTION 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

**Appearance** 

Physical state at 20°C / 101.3kPa : Gas. Colour Colourless

Odour : Poor warning properties at low concentrations.

Diborane

Odour threshold : Odour threshold is subjective and inadequate to warn for overexposure.

Molar mass [g/mol] . 27 7 Melting point [°C] : -165 Boiling point [°C] : -92.5 Critical temperature [°C]

: Not applicable for gases and gas-mixtures. Flash point [°C] : Not applicable for gases and gas-mixtures. Evaporation rate (ether=1)

Flammability range [vol% in air] : 0.8 to 98 Vapour pressure [20°C] : Not applicable. : 0.965 Relative density, gas (air=1)

: 0.42 Relative density, liquid (water=1) Solubility in water [mg/l] : No reliable data available.

Partition coefficient n-octanol/water [ : Not applicable for inorganic gases.

log Pow]

. 38

Decomposition point [°C] 9.2. Other information

Auto-ignition temperature [°C]

Other data : Normally supplied only as a gaseous mixture component.

: 100

# **SECTION 10. Stability and reactivity**

# 10.1. Reactivity

: No reactivity hazard other than the effects described in sub-sections below.

#### 10.2. Chemical stability

: Can form higher boranes. Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

: Can form explosive mixture with air. May react violently with oxidants.

Can ignite spontaneously in air (fire cannot be put out). Can form spontaneous, violently

explosive mixture in air.

# 10.4. Conditions to avoid

: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

#### 10.5. Incompatible materials

: Air, Oxidiser.

For additional information on compatibility refer to ISO 11114

# 10.6. Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.



Page: 7 / 9

Revised edition no: 2 - 01

Date: 25 / 9 / 2012

Supersedes : 20 / 1 / 2011

040

# **Diborane**

# SECTION 10. Stability and reactivity (continued)

# **SECTION 11. Toxicological information**

# 11.1. Information on toxicological effects

Acute toxicity : Delayed fatal pulmonary oedema possible.

Rat inhalation LC50 [ppm/4h] : 40

Skin corrosion/irritation : May cause inflammation of the skin.

Serious eye damage/irritation : Irritation to eyes.

Respiratory or skin sensitisation

Carcinogenicity

: No known effects from this product.

Germ cell mutagenicity

: No known effects from this product.

Reproductive toxicity

: No known effects from this product.

STOT-single exposure

: Damage to kidneys and liver.

Irritation to the respiratory tract.

: Not applicable for gases and gas-mixtures.

STOT-repeated exposure : Damage to kidneys and liver.

# **SECTION 12. Ecological information**

Aspiration hazard

12.1. Toxicity

: No data available.

12.2. Persistence and degradability

: Not applicable for inorganic gases.

12.3. Bioaccumulative potential

: No data available.

12.4. Mobility in soil

: Because of its high volatility, the product is unlikely to cause ground or water pollution.

# 12.5. Results of PBT and vPvB assessment

: No data available.

12.6. Other adverse effects

Effect on ozone layer : None.

**Effect on the global warming** : No known effects from this product.

# **SECTION 13. Disposal considerations**

# 13.1. Waste treatment methods

: Must not be discharged to atmosphere.

Toxic and corrosive gases formed during combustion should be scrubbed before discharge to atmosphere.

Consult supplier for specific recommendations.

Refer to the code of practice of EIGA (Doc. 30/10 "Disposal of Gases, downloadable at http://www.eiga.org) for more guidance on suitable disposal methods



Page: 8/9

Revised edition no: 2 - 01 Date: 25 / 9 / 2012

Supersedes: 20 / 1 / 2011

Diborane

040

# **SECTION 13. Disposal considerations (continued)**

: 16 05 04: Gases in pressure containers (including halons) containing dangerous substances. List of hazardous waste

13.2. Additional information

: None.

# **SECTION 14. Transport information**

**UN** number : 1911

Labelling ADR, IMDG, IATA





: 2.1 : flammable gas. 2.3: Toxic gas.

Land transport (ADR/RID)

H.I. nr

: DIBORANE UN proper shipping name

Transport hazard class(es) : 2 Classification code : 2 TF Packing Instruction(s) : P200

**Tunnel Restriction** : D : Passage forbidden through tunnels of category D and E.

**Environmental hazards** : None.

Sea transport (IMDG)

: DIBORANE Proper shipping name

Class : 2.3 Emergency Schedule (EmS) - Fire : F-D Emergency Schedule (EmS) - Spillage : S-U : P200 **Packing instruction** IMDG-Marine pollutant

Transport in bulk according to Annex : Not applicable.

II of MARPOL 73/78 and the IBC Code

Air transport (ICAO-TI / IATA-DGR)

Proper shipping name (IATA) : DIBORANE

Class : 2.3

Passenger and Cargo Aircraft : DO NOT LOAD IN PASSENGER AIRCRAFT.

Cargo Aircraft only : FORBIDDEN.

Special precautions for user

: - Ensure there is adequate ventilation.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the

In case of emergency: +49 (0)2151 398668

event of an accident or an emergency. Before transporting product containers:

- Ensure that containers are firmly secured.

- Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted.

- Ensure valve protection device (where provided) is correctly fitted.

Avoid transport on vehicles where the load space is not separated from the driver's

compartment.



Page: 9/9 Revised edition no: 2 - 01 Date: 25 / 9 / 2012

Supersedes: 20 / 1 / 2011

040

# Diborane

# **SECTION 14. Transport information (continued)**

#### **SECTION 15. Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU** legislation

Restrictions on use : None. Seveso directive 96/82/EC : Covered

**National legislation** 

: Ensure all national/local regulations are observed.

- 4. BlmschV : Listed.

- Water hazard class WGK (Germany) : 3 - stark wassergefährdend - Other regulations and technical rules : [German regulations]

(not complete)

GefahrstoffV, BetriebssicherheitsV, BGRegel 500 Teil 2.33: Umgang mit Gasen, Technische Regel Gase TRG 280, Technische Regeln Gefährliche Stoffe TRGS 400, 500, 510, 900.

BGR 104, TRBS 2152.

15.2. Chemical safety assessment

: This product is either exempt from REACH, does not meet the minimum volume threshold for

a CSR or the CSA has not yet been carried out.

# **SECTION 16. Other information**

Indication of changes : Revised safety data sheet in accordance with commisssion regulation (EU) No 453/2010

Training advice : Ensure operators understand the flammability hazard. Users of breathing apparatus must be trained.

Ensure operators understand the toxicity hazard.

R12: Extremely flammable. List of full text of R-phrases in section :

section 3.

R26: Very toxic by inhalation. : H220 - Extremely flammable gas.

List of full text of H-statements in H280 - Contains gas under pressure; may explode if heated.

H330 - Fatal if inhaled.

Note This Safety Data Sheet has been established in accordance with the applicable European

Union legislation.

**DISCLAIMER OF LIABILITY** : Before using this product in any new process or experiment, a thorough material compatibility

and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or

damage resulting from its use can be accepted.

End of document