

Page: 1 / 9
Revised edition no: 2 - 01

Date: 19 / 10 / 2012

Supersedes : 22 / 10 / 2010

097B_04

ALPHAGAZ™ AUTO IV OXYGEN (refrigerated)

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : ALPHAGAZ™ AUTO IV OXYGEN (refrigerated)

SDS Nr : 097B_04

Chemical description : Oxygen (refrigerated)

CAS No :7782-44-7 EC No :231-956-9 Index No :008-001-00-8

Registration-No. : Listed in Annex IV / V REACH, exempted from registration.

Chemical formula : O2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.

Test gas / Calibration gas. Laboratory use. Contact supplier for more uses information.

Shield gas for welding processes

Use for manufacture of electronic/photovoltaic components.

Water treatment.

1.3. Details of the supplier of the safety data sheet

Company identification : AIR LIQUIDE Deutschland GmbH

Hans-Günther-Sohl-Straße 5 D-40235 Düsseldorf GERMANY

Telefon: +49 (0)211 6699-0 - Fax: +49 (0)211 6699-222

E-Mail address (competent person) : Info.SDB@AirLiquide.de

1.4. Emergency telephone number

Emergency telephone number : +49 (0)2151 398668

- Availability : (24 / 7)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

• Physical hazards : Oxidizing gases - Category 1 - Danger - (CLP : Ox. Gas 1) - H270

Gases under pressure - Refrigerated liquefied gas - Warning - (CLP : Press. Gas) - H281

In case of emergency: +49 (0)2151 398668

Classification EC 67/548 or EC 1999/45

Classification : O; R8

2.2. Label elements

Labelling Regulation EC 1272/2008 (CLP)

Hazard pictograms





• Hazard pictograms code : GHS03 - GHS04

• Signal words : Danger

• Hazard statements : H270 - May cause or intensify fire; oxidizer.

H281 - Contains refrigerated gas; may cause cryogenic burns or injury.

Precautionary statements



Page: 2 / 9

Revised edition no: 2 - 01

Date: 19 / 10 / 2012

Supersedes: 22 / 10 / 2010

097B 04

ALPHAGAZ™ AUTO IV OXYGEN (refrigerated)

SECTION 2. Hazards identification (continued)

- Prevention : P244 - Keep valves and fittings free from oil and grease

P282 - Wear cold insulating gloves, face shield, eye protection.

P220 - Keep away from combustible materials.

- Response : P336+P315 - Thaw frosted parts with lukewarm water. Do no rub affected area. Get

immediate medical advice / attention.

P370+P376 - In case of fire : Stop leak if safe to do so.

- Storage : P403 - Store in a well-ventilated place.

2.3. Other hazards

Other hazards : None.

SECTION 3. Composition/information on ingredients

3.1. Substance / 3.2. Mixture

Substance.

Substance name		Content [Vol-%]	CAS No EC No Index No Registration no.	Classification(DSD)	Classification(CLP)
Oxygen (refrigerated)	i i	100 %	7782-44-7 231-956-9 008-001-00-8	O; R8	Ox. Gas 1 (H270) Press. Gas (H281)

Contains no other components or impurities which will influence the classification of the product.

- * 1: Listed in Annex IV / V REACH, exempted from registration.
- * 2: Registration deadline not expired.
- * 3: Registration not required: Substance manufactured or imported < 1t/y

Full text of R-phrases see chapter 16. Full text of H-statements see chapter 16

SECTION 4. First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area.

- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain

medical assistance.

- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.

- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

: Continuous inhalation of concentrations higher than 75% may cause nausea, dizziness, respiratory difficulty and convulsion.

In case of emergency: +49 (0)2151 398668

4.3. Indication of any immediate medical attention and special treatment needed

: None.



Page: 3 / 9

Revised edition no: 2 - 01

Date: 19 / 10 / 2012

Supersedes : 22 / 10 / 2010

097B_04

ALPHAGAZ™ AUTO IV OXYGEN (refrigerated)

SECTION 5. Fire-fighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.

- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Exposure to fire may cause containers to rupture/explode.

Supports combustion.

Hazardous combustion products : None.

5.3. Advice for firefighters

Specific methods : If possible, stop flow of product.

If leaking do not spray water onto container. Water surrounding area (from protected position)

to contain fire.

Use fire control measures appropriate to the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering

sewers and drainage systems.

Use water spray or fog to knock down fire fumes if possible.

Special protective equipment for fire

fighters

Gas tight chemically protective clothing in combination with self contained breathing

apparatus.
None necessary.

Standard EN 137 - self-contained open-circuit compressed air breathing apparatus with full

face mask.

EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid

particles. Gas-tight chemical protective suits for emergency teams.

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

: Use protective clothing.

Ensure adequate air ventilation.

Eliminate ignition sources.

Evacuate area.

Prevent from entering sewers, basements and workpits, or any place where its accumulation

can be dangerous. Try to stop release.

Monitor concentration of released product.

6.2. Environmental precautions

: Try to stop release.

6.3. Methods and material for containment and cleaning up

: Liquid spillages can cause embrittlement of structural materials.

Keep area evacuated and free from ignition sources until any spilled liquid has evaporated. (

Ground free from frost).

Ventilate area.

6.4. Reference to other sections

Reference to other sections : See also sections 8 and 13.

Hans-Günther-Sohl-Straße 5 D-40235 Düsseldorf GERMANY Telefon: +49 (0)211 6699-0 - Fax: +49 (0)211 6699-222



Page: 4 / 9

Revised edition no: 2 - 01

Date: 19 / 10 / 2012

Supersedes: 22 / 10 / 2010

097B_04

ALPHAGAZ™ AUTO IV OXYGEN (refrigerated)

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Safe use of the product

Use no oil or grease.

Use only properly specified equipment which is suitable for this product, its supply pressure

and temperature. Contact your gas supplier if in doubt.

Do not smoke while handling product. Keep equipment free from oil and grease.

Use only oxygen approved lubricants and oxygen approved sealings.

Only experienced and properly instructed persons should handle gases under pressure. Ensure the complete gas system was (or is regularily) checked for leaks before use. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. The product must be handled in accordance with good industrial hygiene and safety

procedures.

Consider pressure relief device(s) in gas installations.

Safe handling of the gas receptacle : Suck back of water into the container must be prevented.

Open valve slowly to avoid pressure shock.

Refer to supplier's container handling instructions.

Do not allow backfeed into the container.

Replace valve outlet caps or plugs and container caps where supplied as soon as container is

disconnected from equipment.

Do not remove or deface labels provided by the supplier for the identification of the cylinder

contents.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to repair or modify container valves or safety relief devices.

Keep container valve outlets clean and free from contaminants particularly oil and water. Never use direct flame or electrical heating devices to raise the pressure of a container.

Damaged valves should be reported immediately to the supplier.

7.2. Conditions for safe storage, including any incompatibilities

Storage

: Keep container below 50°C in a well ventilated place.

Segregate from flammable gases and other flammable materials in store. Store containers in location free from fire risk and away from sources of heat and ignition. Stored containers

should be periodically checked for general condition and leakage.

Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion. Containers should be stored in the vertical position and properly secured to prevent toppling. Container valve

guards or caps should be in place. Keep away from combustible materials.

7.3. Specific end use(s)

: None.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

DNEL: Derived no effect level (

: None available.

Workers)

PNEC: Predicted no effect

: None available.

concentration

8.2. Exposure controls

8.2.1. Appropriate engineering controls

: Avoid oxygen rich (>21%) atmospheres.

Provide adequate general and local exhaust ventilation.

Systems under pressure shoud be regularily checked for leakages. Gas detectors should be used when oxidising gases may be released.

Consider work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, : e.g. personal protective equipment

: Protect eyes, face and skin from liquid splashes.

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.

The following recommendations should be considered.

AIR LIQUIDE Deutschland GmbH

Hans-Günther-Sohl-Straße 5 D-40235 Düsseldorf GERMANY Telefon: +49 (0)211 6699-0 - Fax: +49 (0)211 6699-222



Page: 5/9 Revised edition no: 2 - 01 Date: 19 / 10 / 2012

Supersedes: 22 / 10 / 2010

097B 04

In case of emergency: +49 (0)2151 398668

ALPHAGAZ™ AUTO IV OXYGEN (refrigerated)

SECTION 8. Exposure controls/personal protection (continued)

PPE compliant to the recommended EN / ISO standards should be selected.

Wear goggles and a face shield when transfilling or breaking transfer connections • Eye / face protection

Wear safety glasses with side shields Standard EN 166 - Personal eye-protection.

- Hand protection Wear working gloves when handling gas containers.

Standard EN 388 - Protective gloves against mechanical risk.

- Other Consider the use of flame resistant safety clothing. Standard EN ISO 14116 - Limited flame spread materials.

Wear safety shoes while handling containers.

Standard EN ISO 20345 Personal protective equipment - Safety footwear.

Wear cold insulating gloves when transfilling or breaking transfer connections. Thermal hazards

Standard EN 511 - Cold insulating gloves

8.2.3. Environmental exposure

controls

: None necessary.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state at 20°C / 101.3kPa : Gas. Colour : Bluish liquid.

Odour : No odour warning properties.

Odour threshold : Odour threshold is subjective and inadequate to warn for overexposure.

Molar mass [g/mol] : 32 : -219 Melting point [°C] Boiling point [°C] : -183 Critical temperature [°C]

Flash point [°C] : Not applicable for gases and gas-mixtures. Evaporation rate (ether=1) : Not applicable for gases and gas-mixtures.

Flammability range [vol% in air] : Non flammable. : Not applicable. Vapour pressure [20°C] : 1.1

Relative density, gas (air=1) : 1.1 Relative density, liquid (water=1) : 39 Solubility in water [mg/l]

Partition coefficient n-octanol/water [: Not applicable for inorganic gases.

log Pow]

Auto-ignition temperature [°C] : Not applicable. Oxidiser Oxidising properties

- Coefficient of oxygen equivalency (: 1 Ci) ISO10156:

9.2. Other information

Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below

ground level.



Page: 6 / 9

Revised edition no: 2 - 01

Date: 19 / 10 / 2012

Supersedes : 22 / 10 / 2010

097B 04

In case of emergency: +49 (0)2151 398668

ALPHAGAZ™ AUTO IV OXYGEN (refrigerated)

SECTION 10. Stability and reactivity

10.1. Reactivity

: No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Violently oxidises organic material.

Risk of explosion if spilt on organic structural materials (eg wood or asphalt)...

10.4. Conditions to avoid

: None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

: May react violently with combustible materials. May react violently with reducing agents. Consult supplier for specific recommendations.

Consider the potential toxicity hazard due to the presence of chlorinated or fluorinated

polymers in high pressure (> 30 bars) oxygen lines in case of combustion

Keep equipment free from oil and grease.

For additional information on compatibility refer to ISO 11114

10.6. Hazardous decomposition products

: None.

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity : No known toxicological effects from this product.

: No known effects from this product. Skin corrosion/irritation Serious eye damage/irritation : No known effects from this product. Respiratory or skin sensitisation : No known effects from this product. Carcinogenicity : No known effects from this product. Germ cell mutagenicity : No known effects from this product. : No known effects from this product. Reproductive toxicity STOT-single exposure : No known effects from this product. STOT-repeated exposure : No known effects from this product. Aspiration hazard : Not applicable for gases and gas-mixtures.

SECTION 12. Ecological information

12.1. Toxicity

: No ecological damage caused by this product.

12.2. Persistence and degradability

: No ecological damage caused by this product.

12.3. Bioaccumulative potential

: No ecological damage caused by this product.

12.4. Mobility in soil



Page: 7 / 9

Revised edition no: 2 - 01

Date: 19 / 10 / 2012

Supersedes : 22 / 10 / 2010

097B 04

In case of emergency: +49 (0)2151 398668

ALPHAGAZ™ AUTO IV OXYGEN (refrigerated)

SECTION 12. Ecological information (continued)

: No ecological damage caused by this product.

12.5. Results of PBT and vPvB assessment

: Not classified as PBT or vPvB.

12.6. Other adverse effects

: Can cause frost damage to vegetation.

Effect on ozone layer : None.

Effect on the global warming : No known effects from this product.

SECTION 13. Disposal considerations

13.1. Waste treatment methods

: May be vented to atmosphere in a well ventilated place.

Do not discharge into any place where its accumulation could be dangerous.

Consult supplier for specific recommendations

Refer to the code of practice of EIGA (Doc. 30/10 "Disposal of Gases, downloadable at http://

: 16 05 04: Gases in pressure containers (including halons) containing dangerous substances.

www.eiga.org) for more guidance on suitable disposal methods

List of hazardous waste 13.2. Additional information

SECTION 14. Transport information

UN number : 1073

Labelling ADR, IMDG, IATA



: None.



: 5.1 : Oxidizing substances.

2.2 : Non flammable, non toxic gas.

Land transport (ADR/RID)

H.l. nr : 225

UN proper shipping name : OXYGEN, REFRIGERATED LIQUID

Transport hazard class(es) : 2
Classification code : 3 O
Packing Instruction(s) : P203

Tunnel Restriction : C/E Tank carriage: Passage forbidden through tunnels of category C, D and E; Other

carriage: Passage forbidden through tunnels of category E

Environmental hazards : None

Sea transport (IMDG)

Proper shipping name : OXYGEN, REFRIGERATED LIQUID

Class : 2.2
Emergency Schedule (EmS) - Fire : F-C
Emergency Schedule (EmS) - Spillage : S-W
Packing instruction : P203



Page: 8 / 9
Revised edition no: 2 - 01

Date: 19 / 10 / 2012

Supersedes : 22 / 10 / 2010

ALPHAGAZ™ AUTO IV OXYGEN (refrigerated)

097B_04

SECTION 14. Transport information (continued)

IMDG-Marine pollutant : No

Transport in bulk according to Annex : Not applicable.

II of MARPOL 73/78 and the IBC Code

Air transport (ICAO-TI / IATA-DGR)

Proper shipping name (IATA) : OXYGEN, REFRIGERATED LIQUID

Class : 2.

Passenger and Cargo Aircraft : DO NOT LOAD IN PASSENGER AIRCRAFT.

Cargo Aircraft only : FORBIDDEN.

Special precautions for user

: - Ensure there is adequate ventilation.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the

event of an accident or an emergency.

Before transporting product containers:
- Ensure that containers are firmly secured.

- Ensure cylinder valve is closed and not leaking.

- Ensure valve outlet cap nut or plug (where provided) is correctly fitted

- Ensure valve protection device (where provided) is correctly fitted.

Avoid transport on vehicles where the load space is not separated from the driver's

compartment.

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Restrictions on use : None.
Seveso directive 96/82/EC : Listed.

National legislation

: Ensure all national/local regulations are observed.

- 4. BlmschV : Listed.

- Water hazard class WGK (Germany) : NWG - nicht wassergefährdend

- Other regulations and technical rules : [German regulations]

(not complete) Gefahrst

GefahrstoffV, BetriebssicherheitsV, BGRegel 500 Teil 2.33: Umgang mit Gasen, Technische

Regel Gase TRG 280, Technische Regeln Gefährliche Stoffe TRGS 400, 500, 510, 900.

15.2. Chemical safety assessment

: A CSA does not need to be carried out for this product.

SECTION 16. Other information

Indication of changes : Revised safety data sheet in accordance with commisssion regulation (EU) No 453/2010

Training advice : Ensure operators understand the hazard of oxygen enrichment.

List of full text of R-phrases in section: R8: Contact with combustible material may cause fire.

3.

List of full text of H-statements in : H270 - May cause or intensify fire; oxidizer.

section 3. H281 - Contains refrigerated gas; may cause cryogenic burns or injury.

Note : This Safety Data Sheet has been established in accordance with the applicable European

Union legislation.

Hans-Günther-Sohl-Straße 5 D-40235 Düsseldorf GERMANY Telefon: +49 (0)211 6699-0 - Fax: +49 (0)211 6699-222



Page: 9 / 9

Revised edition no: 2 - 01

Date: 19 / 10 / 2012

Supersedes : 22 / 10 / 2010

097B_04

ALPHAGAZ™ AUTO IV OXYGEN (refrigerated)

SECTION 16. Other information (continued)

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document