

Page: 1/9
Revised edition no: 2 - 02
Date: 1/9/2015

Supersedes : 17 / 8 / 2012

089B 04

In case of emergency: +49 (0)2151 398668

ALNAT 1 (refrigerated)

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : ALNAT 1 (refrigerated)

SDS no : 089B_04

Chemical description : Nitrogen (refrigerated)

CAS No :7727-37-9 EC No :231-783-9 Index No :---

Registration-No. : Listed in Annex IV / V REACH, exempted from registration.

Chemical formula : N2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.

Test gas / Calibration gas. Purging. Laboratory use.

Contact supplier for more uses information.

Shield gas for welding processes.
Use for manufacture of electronic/photovoltaic components.

1.3. Details of the supplier of the safety data sheet

Company identification : AIR LIQUIDE Deutschland GmbH

Hans-Günther-Sohl-Straße 5 D-40235 Düsseldorf GERMANY

Telefon: +49 (0)211 6699-0 - Fax: +49 (0)211 6699-222

E-Mail address (competent person) : Info.SDB@AirLiquide.de

1.4. Emergency telephone number

Emergency telephone number : +49 (0)2151 398668

- Availability : (24 / 7)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

• Physical hazards : Gases under pressure - Refrigerated liquefied gas - Warning - (CLP : Press. Gas) - H281

2.2. Label elements

Labelling Regulation EC 1272/2008 (CLP)

· Hazard pictograms



Hazard pictograms code Signal words GHS04 Warning

• Hazard statements : H281 - Contains refrigerated gas; may cause cryogenic burns or injury.

Precautionary statements

- **Prevention** : P282 - Wear cold insulating gloves, face shield, eye protection.

- Response : P336+P315 - Thaw frosted parts with lukewarm water. Do no rub affected area. Get

immediate medical advice / attention.

- Storage : P403 - Store in a well-ventilated place.

2.3. Other hazards



Page: 2 / 9

Revised edition no: 2 - 02

Date: 1 / 9 / 2015

Supersedes: 17 / 8 / 2012

089B 04

ALNAT 1 (refrigerated)

SECTION 2. Hazards identification (continued)

Other hazards : Asphyxiant in high concentrations.

SECTION 3. Composition/information on ingredients

3.1. Substance / 3.2. Mixture

Substance.

Substance name		Content [Vol-%]	CAS No EC No Index No Registration no.	Classification(DSD)	Classification(CLP)
Nitrogen (refrigerated)	:	100 %	7727-37-9		Press. Gas (H281)
			231-783-9		
			+ 4		

Contains no other components or impurities which will influence the classification of the product.

- * 1: Listed in Annex IV / V REACH, exempted from registration.
- * 2: Registration deadline not expired.
- * 3: Registration not required: Substance manufactured or imported < 1t/y Full text of R-phrases see chapter 16. Full text of H-statements see chapter 16

SECTION 4. First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep

victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain

medical assistance.

- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.

- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/ consciousness. Victim may not be aware of asphyxiation.

4.3. Indication of any immediate medical attention and special treatment needed

: None.

SECTION 5. Fire-fighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.

- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products : None

5.3. Advice for firefighters

Specific methods : Move containers away from the fire area if this can be done without risk.

If possible, stop flow of product.

If leaking do not spray water onto container. Water surrounding area (from protected position)

to contain fire.

AIR LIQUIDE Deutschland GmbH

Hans-Günther-Sohl-Straße 5 D-40235 Düsseldorf GERMANY Telefon: +49 (0)211 6699-0 - Fax: +49 (0)211 6699-222

In case of emergency: +49 (0)2151 398668



Page: 3 / 9

Revised edition no: 2 - 02

Date: 1 / 9 / 2015

Supersedes: 17 / 8 / 2012

089B_04

ALNAT 1 (refrigerated)

SECTION 5. Fire-fighting measures (continued)

Use fire control measures appropriate to the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.

Use water spray or fog to knock down fire fumes if possible.

Special protective equipment for fire fighters

: Use self-contained breathing apparatus.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

face mask.

Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire

fighters

Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

: Act in accordance with local emergency plan.

Stay upwind.

Wear self-contained breathing apparatus when entering area unless atmosphere is proved to

be safe

Use protective clothing. Ensure adequate air ventilation.

Evacuate area.

Prevent from entering sewers, basements and workpits, or any place where its accumulation

can be dangerous. Try to stop release.

6.2. Environmental precautions

: Try to stop release.

6.3. Methods and material for containment and cleaning up

: Liquid spillages can cause embrittlement of structural materials.

Ventilate area.

6.4. Reference to other sections

Reference to other sections : See also sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Safe use of the product : Do not breathe gas.

Avoid release of product into atmosphere.

Use only properly specified equipment which is suitable for this product, its supply pressure

and temperature. Contact your gas supplier if in doubt.

Do not smoke while handling product.

Only experienced and properly instructed persons should handle gases under pressure. Ensure the complete gas system was (or is regularily) checked for leaks before use. The product must be handled in accordance with good industrial hygiene and safety procedures.

procedures.

Consider pressure relief device(s) in gas installations.

Safe handling of the gas receptacle : Suck back of water into the container must be prevented. Refer to supplier's container handling instructions.

Do not allow backfeed into the container.

Replace valve outlet caps or plugs and container caps where supplied as soon as container is

disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to repair or modify container valves or safety relief devices.

AIR LIQUIDE Deutschland GmbH

Hans-Günther-Sohl-Straße 5 D-40235 Düsseldorf GERMANY Telefon: +49 (0)211 6699-0 - Fax: +49 (0)211 6699-222

In case of emergency: +49 (0)2151 398668



Page: 4/9 Revised edition no: 2 - 02 Date: 1/9/2015

Supersedes: 17 / 8 / 2012

ALNAT 1 (refrigerated)

089B 04

SECTION 7. Handling and storage (continued)

Keep container valve outlets clean and free from contaminants particularly oil and water. Never use direct flame or electrical heating devices to raise the pressure of a container. Damaged valves should be reported immediately to the supplier.

7.2. Conditions for safe storage, including any incompatibilities

: Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Stored containers should be periodically checked for general condition and leakage.

Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion. Containers should be stored in the vertical position and properly secured to prevent toppling. Container valve guards or caps should be in place. Keep away from combustible materials.

7.3. Specific end use(s)

: None.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

DNEL: Derived no effect level (

Workers)

No data available

PNEC: Predicted no effect

concentration

No data available

8.2. Exposure controls

8.2.1. Appropriate engineering

controls

: Provide adequate general and local exhaust ventilation.

Systems under pressure shoud be regularily checked for leakages.

Oxygen detectors should be used when asphixiating gases may be released.

Consider work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, :

e.g. personal protective equipment

Protect eyes, face and skin from liquid splashes.

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.

The following recommendations should be considered.

PPE compliant to the recommended EN/ISO standards should be selected.

: Wear goggles and a face shield when transfilling or breaking transfer connections · Eye/face protection

Wear safety glasses with side shields Standard EN 166 - Personal eye-protection.

Skin protection

: Wear working gloves when handling gas containers. - Hand protection

Standard EN 388 - Protective gloves against mechanical risk.

- Other Wear safety shoes while handling containers.

Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

: Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be · Respiratory protection

used in oxygen-deficient atmospheres.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

In case of emergency: +49 (0)2151 398668

 Thermal hazards : Wear cold insulating gloves when transfilling or breaking transfer connections.

Standard EN 511 - Cold insulating gloves.

8.2.3. Environmental exposure

controls

: None necessary.



Page: 5 / 9

Revised edition no: 2 - 02

Date: 1 / 9 / 2015

Supersedes: 17 / 8 / 2012

089B 04

ALNAT 1 (refrigerated)

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state at 20°C / 101.3kPa : Gas.

Colour : Colourless liquid.

Odour : No odour warning properties.

Odour threshold : Odour threshold is subjective and inadequate to warn for overexposure.

pH value : Not applicable.

Molar mass [g/mol]: 28Melting point [°C]: -210Boiling point [°C]: -196Critical temperature [°C]: -147

Flash point [°C] : Not applicable for gases and gas-mixtures.

Evaporation rate (ether=1) : Not applicable for gases and gas-mixtures.

Flammability range [vol% in air] : Non flammable.

Vapour pressure [20°C] : Not applicable.

Relative density, gas (air=1) : 0.97
Relative density, liquid (water=1) : 0.8
Solubility in water [mg/l] : 20

Partition coefficient n-octanol/water [: Not applicable for inorganic gases.

log Pow]

Auto-ignition temperature [°C] : Not applicable.

Viscosity at 20°C [mPa.s] : Not applicable.

Explosive Properties : Not applicable.

Oxidising properties : None.

9.2. Other information

Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below

ground level.

SECTION 10. Stability and reactivity

10.1. Reactivity

: No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

: Stable under normal conditions.

10.3. Possibility of hazardous reactions

: None.

10.4. Conditions to avoid

: None under recommended storage and handling conditions (see section 7).

In case of emergency: +49 (0)2151 398668

10.5. Incompatible materials

: None.

For additional information on compatibility refer to ISO 11114

10.6. Hazardous decomposition products

: None.



Page: 6 / 9

Revised edition no: 2 - 02

Date: 1 / 9 / 2015

Supersedes : 17 / 8 / 2012

089B 04

ALNAT 1 (refrigerated)

SECTION 10. Stability and reactivity (continued)

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity : No known toxicological effects from this product.

Skin corrosion/irritation : No known effects from this product. Serious eye damage/irritation : No known effects from this product. Respiratory or skin sensitisation : No known effects from this product. Carcinogenicity : No known effects from this product. Germ cell mutagenicity : No known effects from this product. Reproductive toxicity : No known effects from this product. STOT-single exposure : No known effects from this product. STOT-repeated exposure : No known effects from this product. Aspiration hazard : Not applicable for gases and gas-mixtures.

SECTION 12. Ecological information

12.1. Toxicity

Assessment

No ecological damage caused by this product. No ecological damage caused by this product.

12.2. Persistence and degradability

Assessment : No data available.

12.3. Bioaccumulative potential

Assessment : No data available.

12.4. Mobility in soil

Assessment : No data available.

12.5. Results of PBT and vPvB assessment

: Not classified as PBT or vPvB.

12.6. Other adverse effects

: Can cause frost damage to vegetation.

Effect on ozone layer : None.

Effect on the global warming : No known effects from this product.

SECTION 13. Disposal considerations

13.1. Waste treatment methods

: May be vented to atmosphere in a well ventilated place.

Do not discharge into any place where its accumulation could be dangerous.

Consult supplier for specific recommendations.

Refer to the code of practice of EIGA (Doc. 30/10 "Disposal of Gases, downloadable at http://

www.eiga.org) for more guidance on suitable disposal methods

Ensure that the emission levels from local regulations or operating permits are not exceeded.

In case of emergency: +49 (0)2151 398668

List of hazardous waste codes (from Commission Decision 2001/118/EC)

: 16 05 05: Gases in pressure containers other than those mentioned in 16 05 04.

AIR LIQUIDE Deutschland GmbH



Page: 7/9 Revised edition no: 2 - 02 Date: 1/9/2015

Supersedes: 17 / 8 / 2012

089B 04

In case of emergency: +49 (0)2151 398668

ALNAT 1 (refrigerated)

SECTION 13. Disposal considerations (continued)

13.2. Additional information

: None.

SECTION 14. Transport information

14.1. UN number

UN number : 1977

Labelling ADR, IMDG, IATA



: 2.2 : Non flammable, non toxic gas.

14.2. UN proper shipping name

Transport by road/rail (ADR/RID)

NITROGEN, REFRIGERATED LIQUID

Transport by air (ICAO-TI / IATA-DGR) : NITROGEN, REFRIGERATED LIQUID

Transport by sea (IMDG)

: NITROGEN, REFRIGERATED LIQUID

14.3. Transport hazard class(es)

Transport by road/rail (ADR/RID)

: 2 Class Classification code : 3 A H.I. nr

Tunnel Restriction : C/E Tank carriage: Passage forbidden through tunnels of category C, D and E; Other

carriage: Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Transport by sea (IMDG)

Emergency Schedule (EmS) - Fire : F-C Emergency Schedule (EmS) - Spillage : S-V

14.4. Packing group

Transport by road/rail (ADR/RID) : Not applicable. Transport by air (ICAO-TI / IATA-DGR) : Not applicable. : Not applicable. Transport by sea (IMDG)

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None. Transport by air (ICAO-TI / IATA-DGR) : None. Transport by sea (IMDG) : No

14.6 Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P203

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : Allowed. Packing instruction - Passenger and : 202

Cargo Aircraft



Page: 8/9 Revised edition no: 2 - 02 Date: 1/9/2015

Supersedes: 17 / 8 / 2012

089B 04

ALNAT 1 (refrigerated)

SECTION 14. Transport information (continued)

Cargo Aircraft only : Allowed. Packing instruction - Cargo Aircraft : 202

Transport by sea (IMDG) : P203

Special precautions for user : - Ensure there is adequate ventilation.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the

event of an accident or an emergency. Before transporting product containers - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking.

- Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

Avoid transport on vehicles where the load space is not separated from the driver's

compartment.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Transport in bulk according to Annex : Not applicable. II of MARPOL 73/78 and the IBC Code

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Restrictions on use · None Seveso directive 96/82/EC : Not covered.

National legislation

: Ensure all national/local regulations are observed.

: [German regulations]

BetriebssicherheitsV mit TRBSen insbesondere TRBS 3145 / TRGS 725 "Ortsbewegliche Druckgasbehälter", TRGS 2141, BGRegel 500 Teil 2.33: "Umgang mit Gasen", GefahrstoffV mit Technischen Regeln Gefährliche Stoffe TRGS insbesondere TRGS 407 "Tätigkeiten mit

Gasen - Gefährdungsbeurteilung", TRGS 400, 500, 510, 900.

- 4. BlmschV (Germany)

- Water hazard class (WGK) : WGK Germany: Not hazardous to waters.

15.2. Chemical safety assessment

: A CSA does not need to be carried out for this product.

SECTION 16. Other information

Indication of changes : Revised safety data sheet in accordance with commisssion regulation (EU) No 453/2010

Training advice : The hazard of asphyxiation is often overlooked and must be stressed during operator training. **Further information**

This Safety Data Sheet has been established in accordance with the applicable European Union legislation.

List of full text of H-statements in

section 3.

: H281 - Contains refrigerated gas; may cause cryogenic burns or injury.

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

In case of emergency: +49 (0)2151 398668



Page: 9 / 9

Revised edition no: 2 - 02

Date: 1 / 9 / 2015

Supersedes: 17 / 8 / 2012

089B_04

In case of emergency: +49 (0)2151 398668

ALNAT 1 (refrigerated)

SECTION 16. Other information (continued)

End of document