



# SAFETY DATA SHEET in accordance with REACH regulation 1907/2006/EC

Page : 1 / 9

Revised edition no : 1 - 01

Date : 27 / 2 / 2015

Supersedes : 4 / 8 / 2014

**ARCAL™ Prime (refrigerated)****003B\_03**

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name : ARCAL™ Prime (refrigerated)  
SDS Nr : 003B\_03  
Chemical description : Argon (refrigerated)  
CAS No : 7440-37-1  
EC No : 231-147-0  
Index No : ---  
Registration-No. : Listed in Annex IV / V REACH, exempted from registration.  
Chemical formula : Ar

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.  
Test gas / Calibration gas. Purging. Laboratory use.  
Contact supplier for more uses information. Shield gas for welding processes. Use for  
manufacture of electronic/photovoltaic components. Laser gas.

### 1.3. Details of the supplier of the safety data sheet

Company identification : AIR LIQUIDE Deutschland GmbH  
Hans-Günther-Sohl-Straße 5  
D-40235 Düsseldorf GERMANY  
Telefon: +49 (0)211 6699-0 - Fax: +49 (0)211 6699-222  
E-Mail address (competent person) : Info.SDB@AirLiquide.de

### 1.4. Emergency telephone number

Emergency telephone number : +49 (0)2151 398668  
- Availability : ( 24 / 7 )

## SECTION 2. Hazards identification

### 2.1. Classification of the substance or mixture

#### Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

• Physical hazards : Gases under pressure - Refrigerated liquefied gas - Warning - (CLP : Press. Gas) - H281

#### Classification EC 67/548 or EC 1999/45

Classification : Not included in Annex VI.  
No EC labelling required.  
Not classified as dangerous substance / mixture.

### 2.2. Label elements

#### Labelling Regulation EC 1272/2008 (CLP)

• Hazard pictograms



• Hazard pictograms code : GHS04  
• Signal words : Warning  
• Hazard statements : H281 - Contains refrigerated gas; may cause cryogenic burns or injury.  
• Precautionary statements  
- Prevention : P282 - Wear cold insulating gloves, face shield, eye protection.



# SAFETY DATA SHEET in accordance with REACH regulation 1907/2006/EC

Page : 2 / 9

Revised edition no : 1 - 01

Date : 27 / 2 / 2015

Supersedes : 4 / 8 / 2014

**ARCAL™ Prime (refrigerated)****003B\_03**

## SECTION 2. Hazards identification (continued)

- Response : P336+P315 - Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice / attention.
- Storage : P403 - Store in a well-ventilated place.

### 2.3. Other hazards

- Other hazards : Asphyxiant in high concentrations.

## SECTION 3. Composition/information on ingredients

### 3.1. Substance / 3.2. Mixture

Substance.

Substance name	Content [Vol-%]	CAS No EC No Index No Registration no.	Classification(DSD)	Classification(CLP)
Argon (refrigerated)	: 100 %	7440-37-1 231-147-0 ----- * 1	Not classified (DSD/DPD)	Press. Gas (H281)

Contains no other components or impurities which will influence the classification of the product.

\* 1: Listed in Annex IV / V REACH, exempted from registration.

\* 2: Registration deadline not expired.

\* 3: Registration not required: Substance manufactured or imported &lt; 1t/y

Full text of R-phrases see chapter 16. Full text of H-statements see chapter 16

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

### 4.2. Most important symptoms and effects, both acute and delayed

- : In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/ consciousness. Victim may not be aware of asphyxiation.

### 4.3. Indication of any immediate medical attention and special treatment needed

- : None.



# SAFETY DATA SHEET in accordance with REACH regulation 1907/2006/EC

Page : 3 / 9

Revised edition no : 1 - 01

Date : 27 / 2 / 2015

Supersedes : 4 / 8 / 2014

**ARCAL™ Prime (refrigerated)**

**003B\_03**

## SECTION 5. Fire-fighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

### 5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : None.

### 5.3. Advice for firefighters

- Specific methods : Move containers away from the fire area if this can be done without risk.  
If possible, stop flow of product.  
If leaking do not spray water onto container. Water surrounding area (from protected position) to contain fire.  
Use fire control measures appropriate to the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.  
Use water spray or fog to knock down fire fumes if possible.
- Special protective equipment for fire fighters : Use self-contained breathing apparatus.  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.  
Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.  
Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- : Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.  
Use protective clothing.  
Ensure adequate air ventilation.  
Evacuate area.  
Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.  
Try to stop release.

### 6.2. Environmental precautions

- : Try to stop release.

### 6.3. Methods and material for containment and cleaning up

- : Liquid spillages can cause embrittlement of structural materials.  
Ventilate area.

### 6.4. Reference to other sections

- Reference to other sections : See also sections 8 and 13.



# SAFETY DATA SHEET in accordance with REACH regulation 1907/2006/EC

Page : 4 / 9

Revised edition no : 1 - 01

Date : 27 / 2 / 2015

Supersedes : 4 / 8 / 2014

**ARCAL™ Prime (refrigerated)**

**003B\_03**

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

- Safe use of the product** : Do not breathe gas.  
Avoid release of product into atmosphere.  
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.  
Do not smoke while handling product.  
Only experienced and properly instructed persons should handle gases under pressure.  
Ensure the complete gas system was (or is regularly) checked for leaks before use.  
The product must be handled in accordance with good industrial hygiene and safety procedures.  
Consider pressure relief device(s) in gas installations.
- Safe handling of the gas receptacle** : Suck back of water into the container must be prevented.  
Refer to supplier's container handling instructions.  
Do not allow backfeed into the container.  
Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.  
Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.  
Close container valve after each use and when empty, even if still connected to equipment.  
Never attempt to repair or modify container valves or safety relief devices.  
Keep container valve outlets clean and free from contaminants particularly oil and water.  
Never attempt to transfer gases from one cylinder/container to another.  
Never use direct flame or electrical heating devices to raise the pressure of a container.  
Damaged valves should be reported immediately to the supplier.

### 7.2. Conditions for safe storage, including any incompatibilities

- : Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Stored containers should be periodically checked for general condition and leakage.  
Observe all regulations and local requirements regarding storage of containers.  
Containers should not be stored in conditions likely to encourage corrosion. Containers should be stored in the vertical position and properly secured to prevent toppling. Container valve guards or caps should be in place. Keep away from combustible materials.

### 7.3. Specific end use(s)

- : None.

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

DNEL: Derived no effect level (Workers)

- : No data available.

PNEC: Predicted no effect concentration

- : No data available.

### 8.2. Exposure controls

8.2.1. Appropriate engineering controls

- : Provide adequate general and local exhaust ventilation.  
Systems under pressure should be regularly checked for leakages.  
Oxygen detectors should be used when asphyxiating gases may be released.  
Consider work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

- : Protect eyes, face and skin from liquid splashes.  
A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.  
The following recommendations should be considered.  
PPE compliant to the recommended EN/ISO standards should be selected.

**ARCAL™ Prime (refrigerated)****003B\_03****SECTION 8. Exposure controls/personal protection (continued)**

- **Eye/face protection** : Wear goggles and a face shield when transfilling or breaking transfer connections  
Wear safety glasses with side shields  
Standard EN 166 - Personal eye-protection.
  - **Skin protection**
    - **Hand protection** : Wear working gloves when handling gas containers.  
Standard EN 388 - Protective gloves against mechanical risk.
    - **Other** : Wear safety shoes while handling containers.  
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
  - **Respiratory protection** : Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres.  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
  - **Thermal hazards** : Wear cold insulating gloves when transfilling or breaking transfer connections.  
Standard EN 511 - Cold insulating gloves.
- 8.2.3. Environmental exposure controls : None necessary.

**SECTION 9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

- Appearance**
- Physical state at 20°C / 101.3kPa** : Gas.
  - Colour** : Colourless.
  - Odour** : No odour warning properties.
  - Odour threshold** : Odour threshold is subjective and inadequate to warn for overexposure.
  - pH value** : Not applicable.
  - Molar mass [g/mol]** : 40
  - Melting point [°C]** : -189
  - Boiling point [°C]** : -186
  - Critical temperature [°C]** : -122
  - Flash point [°C]** : Not applicable for gases and gas-mixtures.
  - Evaporation rate (ether=1)** : Not applicable for gases and gas-mixtures.
  - Flammability range [vol% in air]** : Non flammable.
  - Vapour pressure [20°C]** : Not applicable.
  - Relative density, gas (air=1)** : 1.38
  - Relative density, liquid (water=1)** : 1.4
  - Solubility in water [mg/l]** : 67
  - Partition coefficient n-octanol/water [log Pow]** : Not applicable for inorganic gases.
  - Auto-ignition temperature [°C]** : Not applicable.
  - Viscosity at 20°C [mPa.s]** : Not applicable.
  - Explosive Properties** : Not applicable.
  - Oxidising properties** : None.

**9.2. Other information**

- Other data** : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.



# SAFETY DATA SHEET in accordance with REACH regulation 1907/2006/EC

Page : 6 / 9

Revised edition no : 1 - 01

Date : 27 / 2 / 2015

Supersedes : 4 / 8 / 2014

**ARCAL™ Prime (refrigerated)**

**003B\_03**

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

: No reactivity hazard other than the effects described in sub-sections below.

### 10.2. Chemical stability

: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

: None.

### 10.4. Conditions to avoid

: None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

: None.  
For additional information on compatibility refer to ISO 11114

### 10.6. Hazardous decomposition products

: None.

## SECTION 11. Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity	: No known toxicological effects from this product.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Reproductive toxicity	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas-mixtures.

## SECTION 12. Ecological information

### 12.1. Toxicity

Assessment : No ecological damage caused by this product.

### 12.2. Persistence and degradability

Assessment : No ecological damage caused by this product.

### 12.3. Bioaccumulative potential

Assessment : No ecological damage caused by this product.

### 12.4. Mobility in soil

Assessment : No ecological damage caused by this product.

### 12.5. Results of PBT and vPvB assessment

: Not classified as PBT or vPvB.

### 12.6. Other adverse effects

**ARCAL™ Prime (refrigerated)****003B\_03****SECTION 12. Ecological information (continued)**

Effect on ozone layer : Can cause frost damage to vegetation.  
Effect on the global warming : None.

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

List of hazardous waste codes (from Commission Decision 2001/118/EC) : May be vented to atmosphere in a well ventilated place.  
Do not discharge into any place where its accumulation could be dangerous.  
Consult supplier for specific recommendations.  
: 16 05 05: Gases in pressure containers other than those mentioned in 16 05 04.

**13.2. Additional information**

: None.

**SECTION 14. Transport information****14.1. UN number**

UN number : 1951  
Labelling ADR, IMDG, IATA



: 2.2 : Non flammable, non toxic gas.

**14.2. UN proper shipping name**

Transport by road/rail (ADR/RID) : ARGON, REFRIGERATED LIQUID  
Transport by air (ICAO-TI / IATA-DGR) : ARGON, REFRIGERATED LIQUID  
Transport by sea (IMDG) : ARGON, REFRIGERATED LIQUID

**14.3. Transport hazard class(es)**

Transport by road/rail (ADR/RID)  
Class : 2  
Classification code : 3 A  
H.I. nr : 22  
Tunnel Restriction : C/E Tank carriage: Passage forbidden through tunnels of category C, D and E; Other carriage: Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)  
Transport by sea (IMDG)  
Emergency Schedule (EmS) - Fire : F-C  
Emergency Schedule (EmS) - Spillage : S-V

**14.4. Packing group**

Transport by road/rail (ADR/RID) : Not applicable.  
Transport by air (ICAO-TI / IATA-DGR) : Not applicable.  
Transport by sea (IMDG) : Not applicable.



# SAFETY DATA SHEET in accordance with REACH regulation 1907/2006/EC

Page : 8 / 9

Revised edition no : 1 - 01

Date : 27 / 2 / 2015

Supersedes : 4 / 8 / 2014

**ARCAL™ Prime (refrigerated)****003B\_03****SECTION 14. Transport information (continued)****14.5. Environmental hazards**

Transport by road/rail (ADR/RID) : None.  
Transport by air (ICAO-TI / IATA-DGR) : None.  
Transport by sea (IMDG) : No

**14.6 Special precautions for user**

Packing Instruction(s)  
Transport by road/rail (ADR/RID) : P203  
Transport by air (ICAO-TI / IATA-DGR)  
Passenger and Cargo Aircraft : Allowed.  
Packing instruction - Passenger and Cargo Aircraft : 202  
Cargo Aircraft only : Allowed.  
Packing instruction - Cargo Aircraft only : 202  
Transport by sea (IMDG) : P203  
Special precautions for user : - Ensure there is adequate ventilation.  
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.  
Before transporting product containers :  
- Ensure that containers are firmly secured.  
- Ensure cylinder valve is closed and not leaking.  
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.  
- Ensure valve protection device (where provided) is correctly fitted.  
Avoid transport on vehicles where the load space is not separated from the driver's compartment.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

**SECTION 15. Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU legislation**

Restrictions on use : None.  
Seveso directive 96/82/EC : Not covered.

**National legislation**

: Ensure all national/local regulations are observed.  
- 4. BImSchV (Germany)  
- Water hazard class (WGK) : WGK Germany: Not hazardous to waters.  
- Other regulations and technical rules : [German regulations]  
(not complete) BetriebssicherheitsV mit TRBSen insbesondere TRBS 3145 / TRGS 725 "Ortsbewegliche Druckgasbehälter", TRGS 2141, BGR Regel 500 Teil 2.33: "Umgang mit Gasen", GefahrstoffV mit Technischen Regeln Gefährliche Stoffe TRGS insbesondere TRGS 407 "Tätigkeiten mit Gasen - Gefährdungsbeurteilung", TRGS 400, 500, 510, 900.

**15.2. Chemical safety assessment**

: A CSA does not need to be carried out for this product.





**SAFETY DATA SHEET  
in accordance with REACH  
regulation 1907/2006/EC**

Page : 9 / 9

Revised edition no : 1 - 01

Date : 27 / 2 / 2015

Supersedes : 4 / 8 / 2014

**ARCAL™ Prime (refrigerated)**

**003B\_03**

**SECTION 15. Regulatory information (continued)**

**SECTION 16. Other information**

- Indication of changes** : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010
- Training advice** : The hazard of asphyxiation is often overlooked and must be stressed during operator training.
- Further information** : This Safety Data Sheet has been established in accordance with the applicable European Union legislation.
- List of full text of H-statements in section 3.** : H281 - Contains refrigerated gas; may cause cryogenic burns or injury.
- DISCLAIMER OF LIABILITY** : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.  
Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

**End of document**