

Chlorodifluoromethane (R22)**027****SECTION 1. Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Trade name	: Chlorodifluoromethane (R22) , CHLORODIFLUOROMETHANE (R22) N18
SDS Nr	: 027
Chemical description	: Chlorodifluoromethane (R22) CAS No :75-45-6 EC No :200-871-9 Index No :---
Registration-No.	: Registration deadline not expired.
Chemical formula	: CHClF2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	: Industrial and professional. Perform risk assessment prior to use. Test gas / Calibration gas. Laboratory use. Contact supplier for more uses information. Use as refrigerant.
--------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

1.3. Details of the supplier of the safety data sheet

Company identification	: AIR LIQUIDE Deutschland GmbH Hans-Günther-Sohl-Straße 5 D-40235 Düsseldorf GERMANY Telefon: +49 (0)211 6699-0 - Fax: +49 (0)211 6699-222
E-Mail address (competent person)	: Info.SDB@AirLiquide.de

1.4. Emergency telephone number

Emergency telephone number	: +49 (0)2151 398668
- Availability	: (24 / 7)

SECTION 2. Hazards identification**2.1. Classification of the substance or mixture****Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)**


- Physical hazards : Gases under pressure - Liquefied gas - Warning - (CLP : Press. Gas) - H280
- Additional hazards : Dangerous for the ozone layer - Warning - (CLP : Ozone 1 - H420)

Classification EC 67/548 or EC 1999/45

Classification	: N; R59
----------------	----------

2.2. Label elements**Labelling Regulation EC 1272/2008 (CLP)**

- Hazard pictograms



- Hazard pictograms code : GHS07 - GHS04
- Signal words : Warning
- Hazard statements : H280 - Contains gas under pressure; may explode if heated.
H420 - Harms public health and the environment by destroying ozone in the upper atmosphere
- Precautionary statements



SAFETY DATA SHEET in accordance with REACH regulation 1907/2006/EC

Page : 2 / 9

Revised edition no : 2 - 01

Date : 21 / 9 / 2012

Supersedes : 23 / 9 / 2010

Chlorodifluoromethane (R22)**027****SECTION 2. Hazards identification (continued)**

- Storage : P403 - Store in a well-ventilated place.

2.3. Other hazardsOther hazards : Contact with liquid may cause cold burns/frostbite.
Asphyxiant in high concentrations.**SECTION 3. Composition/information on ingredients****3.1. Substance / 3.2. Mixture**

Substance.

Substance name	Content [Vol-%]	CAS No EC No Index No Registration no.	Classification(DSD)	Classification(CLP)
Chlorodifluoromethane (R22)	: 100 %	75-45-6 200-871-9 ----- * 2	N; R59	Liq. Gas (H280) Ozone 1

Contains no other components or impurities which will influence the classification of the product.

* 1: Listed in Annex IV / V REACH, exempted from registration.

* 2: Registration deadline not expired. * 3: Registration not required: Substance manufactured or imported < 1t/y
Full text of R-phrases see chapter 16. Full text of H-statements see chapter 16**SECTION 4. First aid measures****4.1. Description of first aid measures**

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

- : In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/ consciousness. Victim may not be aware of asphyxiation.
In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination.

4.3. Indication of any immediate medical attention and special treatment needed

- : None.



SAFETY DATA SHEET
in accordance with REACH
regulation 1907/2006/EC

Page : 3 / 9

Revised edition no : 2 - 01

Date : 21 / 9 / 2012

Supersedes : 23 / 9 / 2010

Chlorodifluoromethane (R22)

027

SECTION 5. Fire-fighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition : Carbonyl fluoride. Carbon monoxide. Hydrogen fluoride. Phosgene. Hydrogen chloride.

5.3. Advice for firefighters

- Specific methods : If possible, stop flow of product.
Use fire control measures appropriate to the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
Use water spray or fog to knock down fire fumes if possible.
- Special protective equipment for fire fighters : Use self-contained breathing apparatus.
Standard EN 137 - self-contained open-circuit compressed air breathing apparatus with full face mask.
Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
EN 469: Protective clothing for firefighters. EN 659: Protective gloves for firefighters.

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- : Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
Ensure adequate air ventilation.
Evacuate area.
Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
Try to stop release.

6.2. Environmental precautions

- : Try to stop release.

6.3. Methods and material for containment and cleaning up

- : Ventilate area.

6.4. Reference to other sections

- Reference to other sections : See also sections 8 and 13.



SAFETY DATA SHEET in accordance with REACH regulation 1907/2006/EC

Page : 4 / 9

Revised edition no : 2 - 01

Date : 21 / 9 / 2012

Supersedes : 23 / 9 / 2010

Chlorodifluoromethane (R22)**027**

SECTION 7. Handling and storage

7.1. Precautions for safe handling

- Safe use of the product** : Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
Do not smoke while handling product.
Only experienced and properly instructed persons should handle gases under pressure.
Ensure the complete gas system was (or is regularly) checked for leaks before use.
The product must be handled in accordance with good industrial hygiene and safety procedures.
Consider pressure relief device(s) in gas installations.
- Safe handling of the gas receptacle** : Suck back of water into the container must be prevented.
Refer to supplier's container handling instructions.
Do not allow backfeed into the container.
Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
Protect cylinders from physical damage; do not drag, roll, slide or drop.
Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.
When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.
Close container valve after each use and when empty, even if still connected to equipment.
Never attempt to repair or modify container valves or safety relief devices.
Keep container valve outlets clean and free from contaminants particularly oil and water.
Never attempt to transfer gases from one cylinder/container to another.
Never use direct flame or electrical heating devices to raise the pressure of a container.
Damaged valves should be reported immediately to the supplier.

7.2. Conditions for safe storage, including any incompatibilities

- Storage** : Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Stored containers should be periodically checked for general condition and leakage.
Containers should not be stored in conditions likely to encourage corrosion. Containers should be stored in the vertical position and properly secured to prevent toppling. Container valve guards or caps should be in place. Keep away from combustible materials.

7.3. Specific end use(s)

: None.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

- Occupational Exposure Limits**
Chlorodifluoromethane (R22) : ILV (EU) - 8 H - [mg/m³] : 3600
: ILV (EU) - 8 H - [ppm] : 1000
: AGW (8h) - Germany [mg/m³] TRGS 900 : 3600
- DNEL: Derived no effect level (Workers)** : None available.
- PNEC: Predicted no effect concentration** : None available.

8.2. Exposure controls

Chlorodifluoromethane (R22)**027****SECTION 8. Exposure controls/personal protection (continued)**

- 8.2.1. Appropriate engineering controls** : Provide adequate general and local exhaust ventilation.
Systems under pressure should be regularly checked for leakages.
Product to be handled in a closed system.
Ensure exposure is below occupational exposure limits (where available).
Oxygen detectors should be used when asphyxiating gases may be released.
Consider work permit system e.g. for maintenance activities.
- 8.2.2. Individual protection measures, e.g. personal protective equipment** : A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.
The following recommendations should be considered.
PPE compliant to the recommended EN / ISO standards should be selected.
- **Eye / face protection** : Wear safety glasses with side shields or goggles when transfilling or breaking transfer connections
Wear safety glasses with side shields
Standard EN 166 - Personal eye-protection.
 - **Hand protection** : Wear working gloves when handling gas containers.
Standard EN 388 - Protective gloves against mechanical risk.
 - **Other** : Wear safety shoes while handling containers.
Standard EN ISO 20345 Personal protective equipment - Safety footwear.
 - **Respiratory protection** : Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmosphere.
Standard EN 137 - self-contained open-circuit compressed air breathing apparatus with full face mask.
 - **Thermal hazards** : None necessary.
- 8.2.3. Environmental exposure controls** : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

- Appearance**
- Physical state at 20°C / 101.3kPa** : Gas.
- Colour** : Colourless.
- Odour** : Poor warning properties at low concentrations. Ethereal.
- Odour threshold** : Odour threshold is subjective and inadequate to warn for overexposure.
- Molar mass [g/mol]** : 86.5
- Melting point [°C]** : -157
- Boiling point [°C]** : -40.9
- Critical temperature [°C]** : 96.2
- Flash point [°C]** : Not applicable for gases and gas-mixtures.
- Evaporation rate (ether=1)** : Not applicable for gases and gas-mixtures.
- Flammability range [vol% in air]** : Non flammable.
- Vapour pressure [20°C]** : 9.1 bar
- Relative density, gas (air=1)** : 3
- Relative density, liquid (water=1)** : 1.2
- Solubility in water [mg/l]** : 3628
- Partition coefficient n-octanol/water [log Pow]** : 1.08
- Auto-ignition temperature [°C]** : Not applicable.

9.2. Other information



SAFETY DATA SHEET in accordance with REACH regulation 1907/2006/EC

Page : 6 / 9

Revised edition no : 2 - 01

Date : 21 / 9 / 2012

Supersedes : 23 / 9 / 2010

Chlorodifluoromethane (R22)**027****SECTION 9. Physical and chemical properties (continued)**

Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10. Stability and reactivity**10.1. Reactivity**

: No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

: Stable under normal conditions.

10.3. Possibility of hazardous reactions

: None.

10.4. Conditions to avoid

: Heat.

10.5. Incompatible materials

: For additional information on compatibility refer to ISO 11114

10.6. Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11. Toxicological information**11.1. Information on toxicological effects**

Acute toxicity : May produce irregular heart beat and nervous symptoms.
Skin corrosion/irritation : No known effects from this product.
Serious eye damage/irritation : No known effects from this product.
Respiratory or skin sensitisation : No known effects from this product.
Carcinogenicity : No known effects from this product.
Germ cell mutagenicity : No known effects from this product.
Reproductive toxicity : No known effects from this product.
STOT-single exposure : No known effects from this product.
STOT-repeated exposure : No known effects from this product.
Aspiration hazard : Not applicable for gases and gas-mixtures.

SECTION 12. Ecological information**12.1. Toxicity**

EC50 48h - Daphnia magna [mg/l] : 433
EC50 72h - Algae [mg/l] : 377.6
LC50-96h - fish [mg/l] : No data available.

12.2. Persistence and degradability

: Not readily biodegradable.

12.3. Bioaccumulative potential

Chlorodifluoromethane (R22)**027****SECTION 12. Ecological information (continued)**

: Not expected to bioaccumulate due to the low log Kow (log Kow < 4).
Refer to section 9.

12.4. Mobility in soil

: Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5. Results of PBT and vPvB assessment

: Not classified as PBT or vPvB.

12.6. Other adverse effects

Effect on ozone layer : Ozone depletion potential [R11=1] : 0.055
Hazardous to the ozone layer.

Effect on the global warming : Contains Fluorinated greenhouse gases covered by the Kyoto protocol.
Global warming potential [CO2=1] : 1700

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

: Must not be discharged to atmosphere.
Consult supplier for specific recommendations.
Refer to the code of practice of EIGA (Doc. 30/10 "Disposal of Gases, downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods

List of hazardous waste : 14 06 01: Chlorofluorocarbons, HCFC, HFC.

13.2. Additional information

: None.

SECTION 14. Transport information

UN number : 1018

Labelling ADR, IMDG, IATA



: 2.2 : Non flammable, non toxic gas.

Land transport (ADR/RID)

H.I. nr : 20

UN proper shipping name : CHLORODIFLUOROMETHANE (REFRIGERANT GAS R 22)

Transport hazard class(es) : 2

Classification code : 2 A

Packing Instruction(s) : P200

Tunnel Restriction : C/E Tank carriage: Passage forbidden through tunnels of category C, D and E; Other carriage: Passage forbidden through tunnels of category E

Environmental hazards : None.

Sea transport (IMDG)

Proper shipping name : CHLORODIFLUOROMETHANE (REFRIGERANT GAS R 22)

Class : 2.2



SAFETY DATA SHEET in accordance with REACH regulation 1907/2006/EC

Page : 8 / 9

Revised edition no : 2 - 01

Date : 21 / 9 / 2012

Supersedes : 23 / 9 / 2010

Chlorodifluoromethane (R22)**027****SECTION 14. Transport information (continued)**

Emergency Schedule (EmS) - Fire : F-C
Emergency Schedule (EmS) - Spillage : S-V
Packing instruction : P200
IMDG-Marine pollutant : No
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

Air transport (ICAO-TI / IATA-DGR)

Proper shipping name (IATA) : CHLORODIFLUOROMETHANE (REFRIGERANT GAS R 22)
Class : 2.2
Passenger and Cargo Aircraft : Allowed.
Packing instruction - Passenger and Cargo Aircraft : 200
Cargo Aircraft only : Allowed.
Packing instruction - Cargo Aircraft only : 200

Special precautions for user

: - Ensure there is adequate ventilation.
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
Before transporting product containers :
- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.
Avoid transport on vehicles where the load space is not separated from the driver's compartment.

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU legislation**

Restrictions on use : Use of the substance may be subject to registration and authorisation (Regulation 1005/2009).
Seveso directive 96/82/EC : Not covered.

National legislation

: Ensure all national/local regulations are observed.
- 4. BlmschV
- Water hazard class WGK (Germany) : 1 - schwach wassergefährdend
- Other regulations and technical rules : [German regulations]
(not complete) GefahrstoffV, BetriebssicherheitsV, BGR Regel 500 Teil 2.33: Umgang mit Gasen, Technische Regel Gase TRG 280, Technische Regeln Gefährliche Stoffe TRGS 400, 500, 510, 900.

15.2. Chemical safety assessment

: This product is either exempt from REACH, does not meet the minimum volume threshold for a CSR or the CSA has not yet been carried out.



**SAFETY DATA SHEET
in accordance with REACH
regulation 1907/2006/EC**

Page : 9 / 9

Revised edition no : 2 - 01

Date : 21 / 9 / 2012

Supersedes : 23 / 9 / 2010

Chlorodifluoromethane (R22)

027

SECTION 16. Other information

- Indication of changes** : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010
- Training advice** : The hazard of asphyxiation is often overlooked and must be stressed during operator training.
- List of full text of R-phrases in section 3.** : R59 : Dangerous for the ozone layer.
- List of full text of H-statements in section 3.** : H280 - Contains gas under pressure; may explode if heated.
H420 - Harms public health and the environment by destroying ozone in the upper atmosphere
- Note** : This Safety Data Sheet has been established in accordance with the applicable European Union legislation.
- DISCLAIMER OF LIABILITY** : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document