

Hexafluoropropene (R1216)**066****SECTION 1. Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Trade name : Hexafluoropropene (R1216)
SDS Nr : 066
Chemical description : Hexafluoropropene (R1216)
CAS No : 116-15-4
EC No : 204-127-4
Index No : 602-061-00-4
Registration-No. : Registration deadline not expired.
Chemical formula : C₃F₆

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.
Test gas / Calibration gas. Laboratory use.
Contact supplier for more uses information.
Uses advised against : Consumer use

1.3. Details of the supplier of the safety data sheet

Company identification : AIR LIQUIDE Deutschland GmbH
Hans-Günther-Sohl-Straße 5
D-40235 Düsseldorf GERMANY
Telefon: +49 (0)211 6699-0 - Fax: +49 (0)211 6699-222
E-Mail address (competent person) : Info.SDB@AirLiquide.de

1.4. Emergency telephone number

Emergency telephone number : +49 (0)2151 398668
- Availability : (24 / 7)

SECTION 2. Hazards identification**2.1. Classification of the substance or mixture****Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)**

- Health hazards : Acute toxicity, Inhalation - Category 4 - Warning - (CLP : Acute Tox. 4) - H332
Specific Target Organ Toxicity - Single exposure - Category 2 - Warning - (CLP : STOT SE 2) - H371
Specific Target Organ Toxicity - Single exposure - Respiratory tract irritation - Category 3 - Warning - (CLP : STOT SE 3) - H335
Specific Target Organ Toxicity - Repeated exposure - Category 2 - Warning - (CLP : STOT RE 2) - H373
- Physical hazards : Gases under pressure - Liquefied gas - Warning - (CLP : Press. Gas) - H280

Classification EC 67/548 or EC 1999/45

Classification : Xn; R20
Xi; R37

2.2. Label elements**Labelling Regulation EC 1272/2008 (CLP)**

- Hazard pictograms





SAFETY DATA SHEET in accordance with REACH regulation 1907/2006/EC

Page : 2 / 9

Revised edition no : 2 - 01

Date : 22 / 3 / 2013

Supersedes : 8 / 10 / 2010

Hexafluoropropene (R1216)

066

SECTION 2. Hazards identification (continued)

- Hazard pictograms code : GHS08 - GHS07 - GHS04
- Signal words : Warning
- Hazard statements : H280 - Contains gas under pressure; may explode if heated.
H332 - Harmful if inhaled.
H335 - May cause respiratory irritation.
H371 - May cause damage to organs.
H373 - May cause damage to organs through prolonged or repeated exposure.
- Precautionary statements
 - Prevention : P260 - Do not breathe gas, vapours.
 - Response : P304+P340+P315 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice / attention.
P308+P313 - If exposed or concerned : get medical advice.
 - Storage : P403 - Store in a well-ventilated place.

2.3. Other hazards

Other hazards : None.

SECTION 3. Composition/information on ingredients

3.1. Substance / 3.2. Mixture

Substance.

Substance name	Content [Vol-%]	CAS No EC No Index No Registration no.	Classification(DSD)	Classification(CLP)
Hexafluoropropene (R1216)	: 100 %	116-15-4 204-127-4 602-061-00-4 * 2	Xn; R20 Xi; R37	Acute Tox. 4 (H332) STOT SE 3 (H335) STOT SE 2 (H371) STOT RE 2 (H373) Liq. Gas (H280)

Contains no other components or impurities which will influence the classification of the product.

* 1: Listed in Annex IV / V REACH, exempted from registration.

* 2: Registration deadline not expired.

* 3: Registration not required: Substance manufactured or imported < 1t/y

Full text of R-phrases see chapter 16. Full text of H-statements see chapter 16

SECTION 4. First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- Skin contact : Remove contaminated clothing.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

- : In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/ consciousness. Victim may not be aware of asphyxiation.
- In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination.
- Irritation to the respiratory tract.
- Refer to section 11.
- Refer to section 11.

AIR LIQUIDE Deutschland GmbHHans-Günther-Sohl-Straße 5 D-40235 Düsseldorf GERMANY
Telefon: +49 (0)211 6699-0 - Fax: +49 (0)211 6699-222**In case of emergency : +49 (0)2151 398668**



SAFETY DATA SHEET in accordance with REACH regulation 1907/2006/EC

Page : 3 / 9

Revised edition no : 2 - 01

Date : 22 / 3 / 2013

Supersedes : 8 / 10 / 2010

Hexafluoropropene (R1216)

066

SECTION 4. First aid measures (continued)

4.3. Indication of any immediate medical attention and special treatment needed

: Obtain medical assistance.

SECTION 5. Fire-fighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition : Carbonyl fluoride. Carbon monoxide. Hydrogen fluoride.

5.3. Advice for firefighters

- Specific methods : If possible, stop flow of product.
Use fire control measures appropriate to the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
Use water spray or fog to knock down fire fumes if possible.
- Special protective equipment for fire fighters : Use self-contained breathing apparatus.
Standard EN 137 - self-contained open-circuit compressed air breathing apparatus with full face mask.
Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
EN 469: Protective clothing for firefighters. EN 659: Protective gloves for firefighters.

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- : Ensure adequate air ventilation.
Evacuate area.
Gas tight chemically protective clothing in combination with self contained breathing apparatus.
Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
Try to stop release.

6.2. Environmental precautions

- : Try to stop release.

6.3. Methods and material for containment and cleaning up

- : Ventilate area.

6.4. Reference to other sections

- Reference to other sections : See also sections 8 and 13.



SAFETY DATA SHEET in accordance with REACH regulation 1907/2006/EC

Page : 4 / 9

Revised edition no : 2 - 01

Date : 22 / 3 / 2013

Supersedes : 8 / 10 / 2010

Hexafluoropropene (R1216)

066

SECTION 7. Handling and storage

7.1. Precautions for safe handling

- Safe use of the product** : Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
Avoid exposure, obtain special instructions before use.
Do not smoke while handling product.
Avoid suck back of water, acid and alkalis.
Only experienced and properly instructed persons should handle gases under pressure.
Ensure the complete gas system was (or is regularly) checked for leaks before use.
The product must be handled in accordance with good industrial hygiene and safety procedures.
Consider pressure relief device(s) in gas installations.
- Safe handling of the gas receptacle** : Secure gas cylinder against overturning.
Refer to supplier's container handling instructions.
Do not allow backfeed into the container.
Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
Protect cylinders from physical damage; do not drag, roll, slide or drop.
Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.
When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.
Close container valve after each use and when empty, even if still connected to equipment.
Never attempt to repair or modify container valves or safety relief devices.
Keep container valve outlets clean and free from contaminants particularly oil and water.
Never attempt to transfer gases from one cylinder/container to another.
Never use direct flame or electrical heating devices to raise the pressure of a container.
Damaged valves should be reported immediately to the supplier.

7.2. Conditions for safe storage, including any incompatibilities

- Storage** : Secure gas cylinder against overturning.
Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Stored containers should be periodically checked for general condition and leakage.
Observe all regulations and local requirements regarding storage of containers.
Containers should not be stored in conditions likely to encourage corrosion. Containers should be stored in the vertical position and properly secured to prevent toppling. Container valve guards or caps should be in place. Keep away from combustible materials.

7.3. Specific end use(s)

: None.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

DNEL: Derived no effect level (Workers)

- Hexafluoropropene (R1216)** : Inhalation-short term (systemic) [mg/m³] : 46
: Inhalation-long term (systemic) [mg/m³] : 0.62

PNEC: Predicted no effect concentration



SAFETY DATA SHEET in accordance with REACH regulation 1907/2006/EC

Page : 5 / 9

Revised edition no : 2 - 01

Date : 22 / 3 / 2013

Supersedes : 8 / 10 / 2010

Hexafluoropropene (R1216)**066****SECTION 8. Exposure controls/personal protection (continued)**

- Hexafluoropropene (R1216) :
- : Aqua (freshwater) [mg/l] : 0.033
 - : Aqua (marine water) [mg/l] : 0.0033
 - : Aquatic, intermittent releases [mg/l] : 0.334
 - : Sediment, freshwater [mg/kg dw] : 0.279
 - : Sediment, marine water [mg/kg dw] : 0.028
 - : Soil, agricultural [mg/kg dw] : 0.264

8.2. Exposure controls

- 8.2.1. Appropriate engineering controls** : Provide adequate general and local exhaust ventilation.
Alarm detectors should be used when toxic gases may be released.
Systems under pressure should be regularly checked for leakages.
Product to be handled in a closed system.
Ensure exposure is below occupational exposure limits (where available).
Consider work permit system e.g. for maintenance activities.
- 8.2.2. Individual protection measures, e.g. personal protective equipment** : Protect eyes, face and skin from liquid splashes.
A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.
The following recommendations should be considered.
PPE compliant to the recommended EN / ISO standards should be selected.
- **Eye / face protection** : Wear safety glasses with side shields or goggles when transfilling or breaking transfer connections
Wear safety glasses with side shields
Standard EN 166 - Personal eye-protection.
 - **Hand protection** : Wear working gloves when handling gas containers.
Standard EN 388 - Protective gloves against mechanical risk.
 - **Other** : Keep suitable chemically resistant protective clothing readily available for emergency use.
Wear safety shoes while handling containers.
Standard EN ISO 20345 Personal protective equipment - Safety footwear.
 - **Respiratory protection** : Keep self contained breathing apparatus readily available for emergency use.
Standard EN 137 - self-contained open-circuit compressed air breathing apparatus with full face mask.
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
 - **Thermal hazards** : None necessary.
- 8.2.3. Environmental exposure controls** : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

- Appearance
- Physical state at 20°C / 101.3kPa : Gas.
- Colour : Colourless.
- Odour : Poor warning properties at low concentrations.
Ethereal.
- Odour threshold : Odour threshold is subjective and inadequate to warn for overexposure.
- pH value : Not applicable for gas-mixtures.
- Molar mass [g/mol] : 150
- Melting point [°C] : -156
- Boiling point [°C] : -29.6



SAFETY DATA SHEET in accordance with REACH regulation 1907/2006/EC

Page : 6 / 9

Revised edition no : 2 - 01

Date : 22 / 3 / 2013

Supersedes : 8 / 10 / 2010

Hexafluoropropene (R1216)

066

SECTION 9. Physical and chemical properties (continued)

Critical temperature [°C]	: 86.2
Flash point [°C]	: Not applicable for gases and gas-mixtures.
Evaporation rate (ether=1)	: Not applicable for gases and gas-mixtures.
Flammability range [vol% in air]	: Non flammable.
Vapour pressure [20°C]	: 6.4 bar Not applicable.
Relative density, gas (air=1)	: 5.2
Relative density, liquid (water=1)	: 1.3
Solubility in water [mg/l]	: No reliable data available.
Partition coefficient n-octanol/water [log Pow]	: 1.88 Not applicable for gas-mixtures.
Auto-ignition temperature [°C]	: Not applicable.
Viscosity at 20°C [mPa.s]	: Not applicable.
Explosive Properties	: Not applicable.

9.2. Other information

Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.
------------	--

SECTION 10. Stability and reactivity

10.1. Reactivity

: No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

: Stable under normal conditions.

10.3. Possibility of hazardous reactions

: None.

10.4. Conditions to avoid

: None.

10.5. Incompatible materials

: For additional information on compatibility refer to ISO 11114

10.6. Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity	
Rat inhalation LC50 [ppm/4h]	: 2800
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Carcinogenicity	: No known effects from this product.



SAFETY DATA SHEET in accordance with REACH regulation 1907/2006/EC

Page : 7 / 9

Revised edition no : 2 - 01

Date : 22 / 3 / 2013

Supersedes : 8 / 10 / 2010

Hexafluoropropene (R1216)**066****SECTION 11. Toxicological information (continued)**

Germ cell mutagenicity	: No known effects from this product.
Reproductive toxicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: Irritation to the respiratory tract.
STOT-repeated exposure	: May have damaging effect on respiratory system, central nervous system and liver. May cause damage to organs through prolonged or repeated exposure. May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not applicable for gases and gas-mixtures.

SECTION 12. Ecological information**12.1. Toxicity**

: No data available.

12.2. Persistence and degradability: No data available.
Study scientifically unjustified.**12.3. Bioaccumulative potential**: Not expected to bioaccumulate due to the low log Kow (log Kow < 4).
Refer to section 9.**12.4. Mobility in soil**

: Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5. Results of PBT and vPvB assessment

: Not classified as PBT or vPvB.

12.6. Other adverse effects:
May cause pH changes in aqueous ecological systems.

Effect on ozone layer

: None.

Effect on the global warming

: Contains Fluorinated greenhouse gases covered by the Kyoto protocol.

Global warming potential [CO₂=1]

: 16800

SECTION 13. Disposal considerations**13.1. Waste treatment methods**: Avoid discharge to atmosphere.
Do not discharge into any place where its accumulation could be dangerous.
Consult supplier for specific recommendations.
Refer to the code of practice of EIGA (Doc. 30/10 "Disposal of Gases, downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods

List of hazardous waste

: 14 06 01: Chlorofluorocarbons, HCFC, HFC.

13.2. Additional information

: None.

Hexafluoropropene (R1216)**066****SECTION 14. Transport information**

UN number : 1858
Labelling ADR, IMDG, IATA



: 2.2 : Non flammable, non toxic gas.

Land transport (ADR/RID)

H.I. nr : 20
UN proper shipping name : HEXAFLUOROPROPYLENE (REFRIGERANT GAS R 1216)
Transport hazard class(es) : 2
Classification code : 2 A
Packing Instruction(s) : P200
Tunnel Restriction : C/E Tank carriage: Passage forbidden through tunnels of category C, D and E; Other carriage: Passage forbidden through tunnels of category E
Environmental hazards : None.

Sea transport (IMDG)

Proper shipping name : HEXAFLUOROPROPYLENE (REFRIGERANT GAS R 1216)
Class : 2.2
Emergency Schedule (EmS) - Fire : F-C
Emergency Schedule (EmS) - Spillage : S-V
Packing instruction : P200
IMDG-Marine pollutant : No
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

Air transport (ICAO-TI / IATA-DGR)

Proper shipping name (IATA) : HEXAFLUOROPROPYLENE (REFRIGERANT GAS R 1216)
Class : 2.2
Passenger and Cargo Aircraft : Allowed.
Packing instruction - Passenger and Cargo Aircraft : 200
Cargo Aircraft only : FORBIDDEN.
Packing instruction - Cargo Aircraft only : 200

Special precautions for user

: - Ensure there is adequate ventilation.
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
Before transporting product containers :
- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.
Avoid transport on vehicles where the load space is not separated from the driver's compartment.



SAFETY DATA SHEET in accordance with REACH regulation 1907/2006/EC

Page : 9 / 9

Revised edition no : 2 - 01

Date : 22 / 3 / 2013

Supersedes : 8 / 10 / 2010

Hexafluoropropene (R1216)**066****SECTION 15. Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU legislation

Restrictions on use : None.
Seveso directive 96/82/EC : Covered

National legislation

: Ensure all national/local regulations are observed.

- 4. BImSchV
- Water hazard class WGK (Germany) : 1 - Low hazard to waters.
- Other regulations and technical rules : [German regulations]
(not complete) GefahstoffV, BetriebssicherheitsV, BGR Regel 500 Teil 2.33: Umgang mit Gasen, Technische Regel Gase TRG 280, Technische Regeln Gefährliche Stoffe TRGS 400, 500, 510, 900.

15.2. Chemical safety assessment

: This product is either exempt from REACH, does not meet the minimum volume threshold for a CSR or the CSA has not yet been carried out.

SECTION 16. Other information

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010

Training advice : Users of breathing apparatus must be trained.

List of full text of R-phrases in section 3. : R20 : Harmful by inhalation.
R37 : Irritating to respiratory system.

List of full text of H-statements in section 3. : R20 : Harmful by inhalation.
R37 : Irritating to respiratory system.
H280 - Contains gas under pressure; may explode if heated.
H332 - Harmful if inhaled.
H335 - May cause respiratory irritation.
H371 - May cause damage to organs.
H373 - May cause damage to organs through prolonged or repeated exposure.

Further information : H280 - Contains gas under pressure; may explode if heated.
H332 - Harmful if inhaled.
H335 - May cause respiratory irritation.
H371 - May cause damage to organs.
H373 - May cause damage to organs through prolonged or repeated exposure.
: This Safety Data Sheet has been established in accordance with the applicable European Union legislation.
Classification in accordance with calculation methods of regulation (EC) 1272/2008 CLP / (EC) 1999/45 DPD.

Note : This Safety Data Sheet has been established in accordance with the applicable European Union legislation.

DISCLAIMER OF LIABILITY : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document